



	Non-Rated	20-Minute			45-Minute			60-Minute			90-Minute		
	Pressure	Pressure			Pressure			Pressure			Pressure		
	Neutral	Neutral	PPB	PPA	Neutral	PPB	PPA	Neutral	PPB	PPA	Neutral	PPB	PPA
Mortise lock	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Card reader	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Thru-Bolts	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R
Combination lock	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Cylinder Lock	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Concealed vertical rod	OK	OK	OK	OK	OK			OK			OK		
Door bottom	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Door closer - arm only	OK	OK	OK	OK	OK			OK					
Flush cup pull	OK												
Finger pulls	OK												
Hinge rout	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Pivot hinges-top & bottom	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Intermediate pivot	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Mortise dead bolt	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Mortise exit device	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Mortise flush bolt	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Viewers	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Raceway	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Rim exit device	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Roller latch	OK												
Soss hinge	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Wood Bead Lite Kit	OK	OK	OK	OK									
1.375" Thickness	OK												
1.75" Thickness	OK	OK	OK	OK	OK	OK	OK	OK	OK				
2.25" Thickness	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK

Standard pre-machining for all doors includes: 3 hinge preps with prefit and bevelled, prep for cylinder lock.

OK - Available

N/R - Not Required, though available