



**THE MAIMAN COMPANY**

*Fine Architectural Doors*

# Thermal Fused Machining Options

	Non-Rated	20-Minute				45-Minute			60-Minute			90-Minute		
		Thickness				Pressure			Pressure			Pressure		
		1.375"	1.75"			Neutral			Neutral			Neutral		
		Pressure	Neutral	PPB	PPA	Neutral	PPB	PPA	Neutral	PPB	PPA	Neutral	PPB	PPA
		NP, PPA, PPB												
Mortise lock	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Card reader	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Thru-Bolts	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Combination lock	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Cylinder Lock	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Concealed vertical rod	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Door bottom	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Door closer - arm only	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK			
Flush cup pull	OK													
Finger pulls	OK													
Hinge rout	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Pivot hinges-top & bottom	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Intermediate pivot	OK			OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Mortise dead bolt	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Mortise exit device	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Mortise flush bolt	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Viewers	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Raceway	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Rim exit device	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Roller latch	OK													
Soss hinge	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Wood Bead Lite Kit	OK		OK	OK	OK									
6" Firestop Rail	N/R	N/R	N/R	N/R	N/R	OK	OK	OK	OK	OK	OK	OK	OK	OK
5" Firestop Stile	N/R	N/R	N/R	N/R	N/R	OK	OK	OK	OK	OK	OK	OK	OK	OK
5" x 18" Lock Block	N/R	N/R	N/R	N/R	N/R	OK	OK	OK	OK	OK	OK	OK	OK	OK
1.375" Thickness	OK	OK												
1.75" Thickness	OK		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK

Standard pre-machining for all doors includes: 3 hinge preps with predrilled pilot holes, prefit and bevelled, prep for cylinder lock.

OK - Available

N/R - Not Required, though available

For additional information on hardware not shown here or other pre-machining questions please call our engineering department (417) 862-0681 or email us at sales@maiman.com.